U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

160.132 Lifeboat Davits (SOLAS)

ALEVANDED/DVAN MADINE & CAFETY CO	2000 WAYCIDE DRIVE D.O. DOY 2202 HOUGTON TV	
ALEXANDER/RYAN MARINE & SAFETY CO	2000 WAYSIDE DRIVE P.O. BOX 9363 HOUSTON TX	

160.132/0048/0 APPROVED Type PL100 fixed-arm life/rescue boat davit. Maximum safe working load is 10,200 kg.

CALEY OCEAN SYSTEMS MAVOR AVENUE EAST KILBRIDE GLASGOW G74 4PU UNITED KINGDOM

160.132/0037/0 APPROVED Type CD2500 hydraulic motion-damping rescue boat davit for use with CW2500 constant-tension winch; maxi

DAVIT INTERNATIONAL GMBH BERLINER STRASSE 73-75 POSTFACH 1566 D-27226 SULINGEN GERMANY

160.132/0020/0 APPROVED
Type D-NP.70 gravity pivot life/rescue boat davit; maximum safe working load 7,150 kg in ratio 2,770 kg for
Type D-BR.12 single-arm cantilever rescue boat davit, with MSU.45.02 stored mechanical power unit; max. wo
Type D-CR.9,5/4 hydraulic slewing rescue boat davit; maximum safe working load is 9 kN (920 kg) on a single

DAVIT INTERNATIONAL INC. 6311 BREEN ROAD HOUSTON TX 77086

160.132/0024/0 APPROVED Type NDP 79/20 spring-assisted gravity pivot davit; maximum safe working load 8060 kg (4030 kg per davit

ERNST HATECKE GMBH JACHT- UND BOOTSWERFT POSTFACH 1107 D-21703 DROCHTERSEN GERMANY

160.132/0034/0 APPROVED Type FFA 7.4M free-fall lifeboat launching appliance, for use with Hatecke GFF 7.4M lifeboat.

SCHAT-DAVIT COMPANY GMBH P.O. BOX 60 24 69 JARRESTR, 42 2000 HAMBURG 60 GERMANY

160.132/0003/0 APPROVED Type SPG(L) IMO 6560/3870/D gravity pivot davit, approved for a maximum working load of 6,700 kg per se

SOCIETE NOUVELLE ACEBI SAINT-HERBLON 44150 ANCENIS FRANCE

160.132/0040/0 APPROVED Type WELIN-ACEBI RTP 10 stored mechanical power luffing rescue boat davit; maximum safe working load

SURVIVAL SYSTEMS INTERNATIONAL 34140 VALLEY CENTER ROAD P. O. BOX 1855 VALLEY CENTER CA 92082

160.132/0047/0 APPROVED Type PL5002-100 fixed (outrigger) "Hold and Launch Platform" gravity davit; maximum working load 8,180

UMOE SCHAT-HARDING AS N-5470 ROSENDAL

160.132/0031/0 APPROVED Harding type VIP 8 gravity pivot davit for lifeboat or rescue boat use.

UMOE SCHAT-HARDING B.V. P.O. BOX 9032 3506 GA UTRECHT

160.132/0011/0 APPROVED Type SPG(H) 8.5M/3850 gravity pivot davit; maximum working load 8900 kg in ratio 4700 kg aft, 4200 kg for 160.132/0022/0 APPROVED Type SAP 3000/3750 single-arm gravity pivot rescue boat davit; maximum safe working load 2000 kg.

Type NDP 79/20 spring-assisted gravity pivot davit; maximum safe working load 8060 kg (4030 kg per davit maximum safe working load 8060 kg per davit m

UMOE SCHAT-HARDING INC. 912 HIGHWAY 90 EAST NEW IBERIA LA 70560

160.132/0001/1 APPROVED Type SPG(L) IMO 6000/3300 gravity pivot davit; maximum working load 6300 kg per set (3150 kg per 160.132/0002/0 APPROVED Type SPG(VL)-29/16 single-pivot gravity davit; approved maximum working load 29,000 lb per set (14,500 l 160.132/0004/0 APPROVED Type SPG(VL)-27/15 gravity pivot davit; approved for a maximum working load of 27,000 lb per set (13,500 160.132/0007/0 APPROVED Type ORD/DM/6.5 Mk V outrigger gravity davit; approved for a maximum working load of 13,670 lb per set 160.132/0008/0 APPROVED Type MRD/6200-IMO 83 "Miranda" single-arm gravity davit with rescue boat launching cradle; maximum app 160.132/0014/0 APPROVED Type HSA 3500/3700 hydraulic luffing rescue boat davit; maximum safe working load 3500 kg on a single-160.132/0015/0 APPROVED Type SPG(VL) 9.4M/4700 gravity pivot davit for arctic applications. Maximum working load 28,000 lbs eve 160.132/0017/0 APPROVED Type SA/ORD/3000/R6 outrigger gravity rescue boat davit. Maximum safe working load 3000 kg on a singl 160.132/0018/0 APPROVED Type SA/ORD/3000/R6-R5 outrigger gravity rescue boat davit. Maximum safe working load 3000 kg on singl 160.132/0025/0 APPROVED Type ORD/UDM/8500/7.5 fixed davit for under-deck mounting; maximum safe working load 10,000 kg using

Page 270 of 395

Note: Based on data as of March 1, 1998

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION "Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

160.132/0026/0	APPROVED	Type SPG(L) 9600/4870 gravity pivot davit with spring assist; maximum safe	working load 10,000 kg (5,000 k	
160.132/0030/0	APPROVED	Type GRA/17/13/8.0M gravity trackway davit; approved for a maximum safe	working load of 7318 kg (3659	
160.132/0035/0 [/]	APPROVED	Type SPG (SP) 3650/7.5 gravity pivot davit with spring assist; maximum safe	working load 8,000 kg (4,000 kg	
UMOE SCHAT-HAI	RDING LTD. OFF	SHORE DIVISION MUMBY ROAD GOSPORT, HAMPSHIRE		
160.132/0012/0	APPROVED	Type SPG (H) 9.4M/4700 gravity pivot davit. Maximum working load 12500 kg	in ratio 6745 kg aft, 5755 kg fo	
160.132/0013/0	APPROVED	Type MRT/2500, MRT/3000, or MRT/3900 "Miranda" triple point gravity davit	with rescue boat launching cra	
160.132/0016/0	APPROVED	Type ORD/DM/8500/7.5M or ORD/DM/9500/8.5M outrigger davit; maximum safe	e working load 10,000 kg u	
160.132/0019/0	APPROVED	Schat type SPR 12.0 stored mechanical power rescue boat davit; approved for	a maximum working load of 12	
160.132/0023/0	APPROVED	Type SPG(VL) 7.5/13.5 gravity pivot davit with spring assist; maximum safe	e working load 7,950 kg in ratio	
160.132/0029/0	APPROVED	Type ORD/12500/9.4 outrigger gravity davit; maximum working load 12500 kg	in ratio 6400 kg aft, 6100 kg fo	
VESTDAVIT A/S	C. SUNDTSGT. 37	N-5004 BERGEN NORWAY		
160.132/0027/0	APPROVED	Vestdavit PL-1500 hydraulic luffing rescue boat davit; approved for a maxim	mum working load of 1500 kg on	
160.132/0038/0	APPROVED	Type Vestdavit H-5000 hydraulic luffing life/rescue boat davit; maximum wo	rking load 5000 kg on single-part	
160.132/0041/0	APPROVED	Type HSA 3500/3700 hydraulic luffing rescue boat davit; maximum safe	vorking load 3500 kg on a single-	
WELIN LAMBIE LII	MITED ROITANN	IIA HOUSE OLD BUSH STREET WEST MIDLANDS BRIERLEY HILL UNITE	D KINGDOM	
160.132/0043/0		Type OHGD 75 overhead gravity trackway davit with hydraulic bowsing system;	maximum safe working load 1	
160.132/0044/0 [/]	APPROVED	Type SARB 1.0A single-arm hydraulic slewing rescue boat davit; maximum safe	working load 1080 kg on a sin	
UMOE SCHAT-HARDING INC. 912 HIGHWAY 90 EAST NEW IBERIA LA 70560				
160.132/0010/0 F		Type SPG(VL)-27/15 gravity pivot davit; approved for a maximum working load	of 27,000 lbs. per set (13,500 l	
130.102/0010/0		1,750 St. S(12, 21, 10 gravity pivot davit, approved for a maximum working load	5. 21,500 ibs. por 50t (10,000 i	
VESTDAVIT A/S C. SUNDTSGT. 37 N-5004 BERGEN NORWAY				
160.132/0028/0 F	FORMER-MAY USE	Vestdavit PL-1500 hydraulic luffing rescue boat davit; approved for a maxim	mum working load of 1500 kg on	

Page 271 of 395 Note: Based on data as of March 1, 1998